




125B


Efficient hand held blower that combines high blowing power with user friendliness. Perfect for home owners.

Well balanced and easy to manoeuvre thanks to in-lined air out let.



IN LINED OUTLET

The fan housing is designed so that the air stream is in lined with the handle. This makes the machine very easy to manoeuvre.



AUTO RETURN STOP SWITCH

Stop switch automatically resets to the ON position for trouble-free starting.



CRUISE CONTROL

Fan speed can be set for easier handling.



ADJUSTABLE TUBE LENGTH

The blowing tube length is adjustable for best performance.

Features

- Intuitive controls
- Fuel pump for easy starting

Technical data

| | |
|---|-------------------------------------|
| Cylinder displacement | 28 cm ³ / 1.7 cu. inch |
| Power output | 0.8 kW |
| Maximum power speed | 8000 rpm |
| Fuel tank volume | 0.5 lit / 16.91 fl oz |
| Fuel consumption | 575 g/kWh |
| Spark plug | Champion RCJ6Y |
| Air flow in housing | 13.31 m ³ /min / 470 cfm |
| Air flow in pipe | 12.03 m ³ /min / 425 cfm |
| Air speed | 76 m/s / 170 mph |
| Air speed (round nozzle) | 58.12 m/s / 130 mph |
| Air speed (flat nozzle) | 76 m/s / 170 mph |
| Equivalent vibration level (ahv, eq) handle | 11.1 m/s ² |
| Sound pressure level at operators ear | 92 dB(A) |
| Sound power level, guaranteed (LWA) | 107 dB(A) |
| OEM Harness | – |
| OEM Nozzle type | Round+ Flat |
| Weight | 4.26 kg / 9.4 lbs |

ARTICLES

| | | | |
|--------------|------------------|----------|----------|
| 952 71 56-43 | All ex US50, CAN | € 276.41 | € 349.99 |
|--------------|------------------|----------|----------|

