



## LC 353V

LC 353V is a walk-behind lawn mower that creates a fantastic cutting result and lawn appearance thanks to its AFTech™ technology: the cutting blade is engineered to create an upward airflow as it rotates. This airflow lifts up the grass in order to create an evenly cut lawn. Then, the airflow transports the grass clippings through the chute into the collector. This process fills the collector extremely efficiently, enabling you to cut for a long time without interruption. LC 353V has a durable design to last for many years. It features AutoWalk™ 2 for ergonomic and comfortable speed control.



### BRIGGS STRATTON ENGINE WITH READYSTART

The ReadyStart system eliminates the need to manually prime or choke the engine. It also reduces resistance in the starter cord by 30%, making the mower very easy to start.



### AFTECH™

AFTech is a unique design where the cutting deck, blade and chute produce optimum air flow. This means first-class results in all cutting modes. When collecting it helps fill the collector to the optimum level, so there is less emptying.



### AUTOWALK™ 2

The two-hand speed control makes it possible to shift between using right or left hand for the variable speed adjustment. This ensures ergonomic operation and also makes it easier to mow along hedges and around obstacles, as you can release the grip of one hand and the mower keeps running.



### ROBUST DESIGN

The cutting deck comes in one piece straight out of the stamping line which means it has no welded parts. This gives high torsional rigidity, tolerance and durability as well as sturdiness in operation.

## Features

- Central cutting height adjustment
- BioClip® kit available as accessory
- Variable drive speed for easy speed adjustment
- Two-position handle height adjustment
- Foldable handle for easy storage
- Easy-to-start B&S DOV engine
- Double ball-bearing wheels for a smooth run
- Aggressive wheel tread for optimum traction
- Easy-to-handle collector
- Down-drafted vents for reduced dust and noise
- Durable zinc-plated steel cutting deck
- Stainless steel bumper protects the front
- Service hatch for easy cleaning.
- Water hose connection for easy cleaning
- Safety grip

## Technical data

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Engine manufacturer                   | Briggs & Stratton                  |
| Engine type                           | DOV                                |
| Engine name                           | 750e DOV Series                    |
| Cylinder displacement                 | 161 cm <sup>3</sup> / 9.8 cu. inch |
| Net power at preset rpm               | 2.7 kW @ 2900 rpm                  |
| Fuel tank volume                      | 1 lit / 0.26 gal.                  |
| Drive system                          | AutoWalk™ 2                        |
| Drive wheels                          | Rear                               |
| Speed forward, min-max                | 0-5.4 km/h / 0-3.4 mph             |
| Speed                                 | 5.4 km/h                           |
| Cutting deck material                 | Zinc-plated steel                  |
| Cutting methods                       | Collection/Rear ejection           |
| BioClip® kit                          | Available as accessory             |
| Cutting width                         | 53 cm / 21 inch                    |
| Cutting height, min-max               | 25 - 75 mm / 1 - 3 inch            |
| Cutting height steps                  | 5                                  |
| Cutting height adjustment             | Central                            |
| Collector type                        | Down-vented hard bag               |
| Collector volume                      | 60 lit / 2.1 cu. feet              |
| Handle type                           | Comfort                            |
| Handle height adjustment              | Quick-set (2 steps)                |
| Wheel bearing, front/rear             | Yes/Yes                            |
| Foldable handlebar                    | Yes                                |
| Water hose connection                 | Yes                                |
| Wheel size, front/rear                | 210 mm/210 mm / 8.3 inch/8.3 inch  |
| Weight                                | 41 kg / 90.4 lbs                   |
| Sound pressure level at operators ear | 84 dB(A)                           |
| Sound power level, measured           | 98 dB(A)                           |
| Sound power level, guaranteed (LWA)   | 98 dB(A)                           |

### ARTICLES

967 23 91-01

LC 353V

€ 799.99

