



Husqvarna®

New!



## 129RJ

Professionals turn to Husqvarna for powerful engines that make tough jobs easy. With Husqvarna Brushcutter 129RJ, that power is available to consumers as well. Brushcutter 129RJ features a powerful 27cc engine and professional quality – combined with a focus on ease of use. It is easy to start thanks to Smart Start®, intuitive controls and the automatic stop return switch – a feature that automatically resets to the ON position for trouble-free starting. 129RJ comes with trimmer head and grass blade plus a combination guard so you don't have to switch guard.



### INTUITIVE CONTROLS

The choke and purge are easy to reach and understand.



### J-HANDLE

Equipped with J-handle for greater versatility.



### FUEL PUMP

Fuel pump designed for easy starting.



### SMART START®

The engine and starter have been designed so the machine starts quickly with minimum effort. Resistance in the starter cord is reduced by up to 40%.

## Features

- Standard harness for lighter brushcutters
- Auto return stop switch for easy starting
- Grass bevel gear for best cutting performance
- Tap 'n Go trimmer head

## Technical data

Cylinder displacement	27.5 cm <sup>3</sup> / 1.68 cu.inch
Power output	0.85 kW
Maximum power speed	8000 rpm
Fuel tank volume	0.343 lit / 11.5 fl oz
Fuel consumption	495 g/kWh
Idling speed	3200 rpm
Spark plug	NGK CMR6A
Electrode gap	0.5 mm / 0.02"
Clutch engagement speed	4200 rpm ( $\pm 120$ rpm)
Maximum rpm output shaft	10500 rpm
Output shaft thread	M10x1.25V
Equivalent vibration level (ahv, eq) front / rear handle	0/0 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) left / right handle	4.21/4.23 m/s <sup>2</sup>
Sound pressure level at operators ear	94 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
OEM Trimmer head	T25 (L)
OEM Grass blade	Grass 255-4
OEM Harness	Single harness
Weight (excl. cutting equipment)	4.76 kg / 10.49 lbs

### ARTICLES

967 19 34-01	T25+Grass 255-4, All ex US50, CAN	€ 379.99
--------------	-----------------------------------	----------

