




R 422Ts AWD

High performance All-Wheel-Drive Rider, built on an operator-friendly chassis. Equipped with convenient features like power steering, hydraulic tool lift, headlights and quick tool connection for hassle-free and efficient tool changes. Can be fitted with a flail mower, broom, snow thrower, snow blade and more. An excellent choice for private estate owners, sports facilities and hotels with large areas to maintain year-round. The Rider 422Ts AWD is delivered deckless and can be fitted with 103, 112 and 122 cm Combi cutting decks offering BioClip and rear ejection.



UNIQUE ARTICULATED STEERING

The unique articulated steering system allows the rear pair of wheels to swing in underneath the machine. The result is superior manoeuvrability with a minimum turning radius at full lock.



ATTACHMENT FRAME

Easy to shift between cutting decks and front-mounted attachments, such as broom, flail mower, snow blade and snow thrower.



EXTERNAL FUEL CAP

Thanks to the external fuel cap, you don't have to open the engine hood when taking on more fuel. The extra wide fuel tank opening makes refueling even easier.



PEDAL-OPERATED HYDROSTATIC TRANSMISSION

Easy speed and direction control with pedal-operated hydrostatic transmission. Separate pedals for forward and reverse.

Features

- Three-blade cutting deck
- Comfortable driver's position
- Easy-access controls for user comfort
- Automatic blade engagement
- Easy-access cutting height lever
- Equally sized wheels for a comfortable ride
- Engine behind driver for better overview
- Floating cutting deck for reduced risk of scalping
- Pivoting support wheels on the cutting deck
- Power steering makes more enjoyable drive
- Adjustable pitch angle for optimum cutting deck position
- Height adjustable steering wheel
- Pivoting rear axle for maximum traction
- 12V socket outlet for electric equipment
- Hour meter
- Oil-cooled hydraulic system
- Front-mounted deck for optimum accessibility
- All-Wheel Drive secure traction on all areas
- Improved performance by hydraulic tool lift
- Accessories for versatile year-round usage
- Welded steel chassis for optimum stiffness
- Dual hydrostatic transmissions secure traction
- Enlarged space for a more comfort drive
- Comfortable high-back premium seat
- Easy fuel level check by transparent fuel tank
- Easy tool exchange by unique quick coupling
- Service position for easy deck maintenance
- All controls collected on a control panel
- Halogen headlights provide efficient light
- Tilting hood makes maintenance quick and easy
- Practical carrier for extra equipment
- BioClip® mode for frequently cut areas
- Rear ejection cutting mode for rougher areas

Technical data

Engine manufacturer	Briggs & Stratton
Engine name	Endurance Series V-Twin
Net power at rated rpm	12.6 kW @ 3000 rpm
Cylinder displacement	656 cm ³ / 40 cu.inch
Cylinders	2
Engine cooling	Air
Generator	16 A
Battery	12 V 24 Ah
Fuel type	Gasoline
Fuel tank volume	17 lit / 4.5 gal.
Engine lubrication type	Full pressure
Oil filter	Yes
Transmission type	Hydrostatic AWD
Transmission manufacturer, front	Kawasaki
Transmission model, front	KTM100
Transmission manufacturer, rear	Kawasaki
Transmission model, rear	K664
Transmission manufacturer	Kawasaki
Drive method	Pedal-operated
Speed forward, min-max	0-11 km/h (0-8 mph)
Speed reverse, min-max	0-7 km/h (0-4.3 mph)
Safety limit slopes	10°
Uncut circle	60 cm / 23.6 inch ¹⁾
Cutting width, Min-Max	103-122 cm (41-48 inch)
Optional cutting decks	Combi 112, Combi 122, Combi 103
Cutting deck type	Combi
Cutting deck material	Steel
Cutting methods	BioClip®/Rear discharge
Cutting height, min-max	25-75 mm (1-3 inch)
Cutting height steps	7 pcs
Blade engagement	Automatic
Blades	3
Powder-coated cutting deck	Yes
Oil cooler	Yes
Hour meter	Digital with pre-programmed service intervals
Seat material	Vinyl
Seat suspension	Yes
Seat back height	High
Hinged arm rest	Standard
Foldable seat	Yes
Tyre dimensions, front	200/65-8
Tyre dimensions, rear	200/65-8
Wheelbase	100 cm / 39.4"
Ground clearance	90 mm / 3.54 inch
Base machine, length	207 cm / 81.5 inch
Base machine, width	90 cm / 35.4 inch
Base machine, height	116 cm / 45.7 inch
Weight	330 kg / 727.5 lb
Gross weight towed	150 kg / 330.5 lb ¹⁾
Sound pressure level at operator's ear	88 dB(A)
Sound power level, measured	102 dB(A)
Sound power level, guaranteed (LWA)	103 dB(A)
Vibration level steering wheel	3.5 m/s ²
Vibration level seat	0.7 m/s ²

1) Measured on trim side turn! For 2-wheel drive machines, towing of trailer is only allowed in dry conditions and on flat surfaces. Be aware that towing of trailer may shorten the life time of the Rider's transmission.

ARTICLES			
966 63 25-01	R 422T AWD (-2011)	€ 8,048.77	€ 11,659.99

