



R 213C

Efficient Rider with 94 cm Combi cutting deck, offering first-class BioClip® and rear ejection cutting. Suitable for home- and landowners who require high efficiency, ease of use, superior manoeuvrability and a truly enjoyable ride. The articulated steering system and front-mounted cutting deck means intuitive operation, excellent mowing accessibility and great overview of your working area. Pedal-operated hydrostatic transmission, easy-access controls and automatic blade engagement, makes mowing a pleasure. The cutting deck is easily tilted up into service position for easy cleaning after mowing. This Rider can do so much more than cutting your lawn. Thanks to attachments such as snow blade, trailer, moss rake and spreader, it can maintain your garden all year round.




UNIQUE ARTICULATED STEERING

The unique articulated steering system allows the rear pair of wheels to swing in underneath the machine. The result is superior manoeuvrability with a minimum turning radius at full lock.



FRONT-MOUNTED CUTTING DECK

Front-mounted cutting deck for excellent accessibility into corners and under bushes, park benches etc.



COMBI CUTTING DECK

The Combi cutting deck offers the versatility of two different cutting systems. Choose between BioClip® for lawn fertilisation and rear ejection for efficient mowing on areas with higher and rougher grass.



SERVICE POSITION

Service position on the cutting deck facilitates cleaning and service.

Features

- Three-blade cutting deck
- Comfortable driver's position
- Accessories for versatile year-round usage
- External fuel cap for easy refueling
- Pedal-operated hydrostatic transmission
- Easy-access controls for user comfort
- Automatic blade engagement
- Easy-access cutting height lever
- BioClip® mode for frequently cut areas
- Rear ejection cutting mode for rougher areas
- Equally sized wheels for a comfortable ride
- Engine behind driver for better overview
- Adjustable pitch angle for optimum cutting deck position
- Tilting hood makes maintenance quick and easy
- Easy fuel level check by transparent fuel tank
- Pivoting rear axle for maximum traction
- Easy-access storage compartment
- Bottle holder

Technical data

Engine manufacturer	Briggs & Stratton
Engine name	Intek
Net power at preset rpm	6.7 kW @ 3000 rpm
Cylinder displacement	344 cm ³ / 20.99 cu.inch
Cylinders	1
Engine cooling	Air
Generator	3 A
Battery	12 V 24 Ah
Fuel Type	Gasoline
Fuel tank volume	12 lit / 3.2 gal.
Engine lubrication type	Pressure
Oil filter	Yes
Transmission type	Hydrostatic
Transmission manufacturer	Tuff Torq
Transmission model	K46
Drive method	Pedal-operated
Speed forward, min-max	0-9 km/h / 0-5.6 mph
Speed reverse, min-max	0-9 km/h / 0-5.6 mph
Safety limit slopes	10 °
Uncut circle	30 cm / 11.8 inch ¹
Cutting width	94 cm / 37 inch
Cutting deck type	Combi
Cutting deck material	Steel
Cutting methods	BioClip®/Rear discharge
Cutting height, min-max	25 - 75 mm / 1 - 3 inch
Cutting height steps	10 pcs
Blade engagement	Automatic
Blades	3
Powder-coated cutting deck	Yes
Seat material	Vinyl
Seat back height	Medium
Foldable seat	Yes
Tyre dimensions, front	165/60-8
Tyre dimensions, rear	165/60-8
Wheelbase	88.7 cm / 34.9"
Ground clearance	105 mm / 4.1 inch
Base machine, length	223 cm / 87.8 inch
Base machine, width	100 cm / 39.37 inch
Base machine, height	107 cm / 42.1 inch
Weight	229 kg / 504.9 lbs
Gross weight towed	110 kg / 242.5 lbs ¹
Sound pressure level at operators ear	84 dB(A)
Sound power level, measured	98 dB(A)
Sound power level, guaranteed (LWA)	100 dB(A)
Vibration level steering wheel	2.5 m/s ²
Vibration level seat	0.7 m/s ²

1) Measured on trim side turn1) For 2-wheel drive machines, towing of trailer is only allowed in dry conditions and on flat surfaces. Be aware that towing of trailer may shorten the life time of the Rider's transmission.

ARTICLES

967 15 04-01

R 213C (2013-)

€ 4,499.99

