



## 455 Rancher

The 455 Rancher is an ideal saw for landowners and part-time users who require a high powered, heavy-duty and responsive workmate for all cutting conditions. It combines the best characteristics of its predecessor with new, facilitating technology and ergonomics.




### **X-TORQ®**

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.




### **QUICK-RELEASE AIR FILTER**

Facilitates cleaning and replacement of the air filter.



### **COMBINED CHOKE/STOP CONTROL**

Combined choke/stop control allow for easier starting and reduce the risk of engine flooding.



### **AIR INJECTION**

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.

## Features

- Quick and easy chain adjustment
- Maximum durability for tough applications
- Ergonomic grip with angled front handle
- LowVib® sparing the user's arms and hands
- Adjustable chain oil pump
- Felling marks for correct felling direction
- Smart Start® for easy starting
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	55.5 cm <sup>3</sup> / 3.4 cu.inch
Power output	2.6 kW
Maximum power speed	9000 rpm
Fuel tank volume	0.44 lit / 14.88 fl oz
Fuel consumption	407 g/kWh
Idling speed	2700 rpm
Spark plug	NGK BPMR7A, Champion RCJ7Y
Electrode gap	0.5 mm / 0.02"
Torque, max.	3.2 Nm / 6600 rpm
Oil tank volume	0.32 lit / 0.7 US pint
Oil pump type	Automatic
Equivalent vibration level (ahv, eq) front / rear handle	3.4 / 4.5 m/s <sup>2</sup>
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Chain pitch	3/8"
Chain speed at 133% of maximum engine power speed	26.6 m/s / 87.27 fts
Recommended bar length, min-max	33-50 cm / 13"-20"
Weight (excl. cutting equipment)	5.8 kg / 12.8 lbs

### ARTICLES

965 03 01-18	18" SN - .325 - H25 - All markets	€ 709.99
--------------	-----------------------------------	----------

