



435

Second generation lightweight and efficient all-round saw ideal for those looking for a chainsaw that is exceptionally easy to start and manoeuvre. Starts easily also with a slower pull, comes with flip-up tank caps. Featuring X-Torq® engine for lower fuel consumption and reduced emission levels. Equipped with fuel pump and Auto return stop switch for easier starting.



AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



QUICK-RELEASE AIR FILTER

Facilitates cleaning and replacement of the air filter.



FLIP-UP TANK CAP

The flip-up tank cap is easy to open and close when refueling.

Features

- Ergonomic soft grip rear handle
- Felling marks for correct felling direction
- Quick and easy chain adjustment
- Maximum durability for tough applications
- Fuel level window
- Easy to start
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake
- Easy to maintain with snap locked cylinder cover
- LowVib® sparing the user's arms and hands

Technical data

Cylinder displacement	40.9 cm ³ / 2.5 cu.inch
Power output	1.6 kW
Maximum power speed	9000 rpm
Fuel tank volume	0.37 lit / 12.51 fl oz
Fuel consumption	652 g/kWh
Idling speed	2900 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A
Electrode gap	0.5 mm / 0.02"
Torque, max.	2 Nm/6300 rpm
Oil tank volume	0.25 lit / 0.5 US pint
Oil pump type	Fixed flow
Equivalent vibration level (ahv, eq) front / rear handle	2.5/3.2 m/s ²
Sound pressure level at operators ear	102 dB(A)
Sound power level, guaranteed (LWA)	114 dB(A)
Chain pitch	.325"
Chain speed at 133% of maximum engine power speed	23 m/s / 75.46 ft/s
Recommended bar length, min-max	33-46 cm / 13"-18"
Chain gauge	0.05"
Weight(excl. cutting equipment)	4.2 kg / 9.2 lbs

ARTICLES

967 15 54-35	15" - .325 - SN - H30 - Europe West	€ 459.99
--------------	-------------------------------------	----------

